



Color Variants

BM450110
Stainless steel-backed full glass door
Width 60 cm

Included accessories

1 x combination grid.
1 x glass tub.

Installation Accessories

BA476310
Handle bar, stainless steel

Product Variants

BM451110
Combi-microwave oven 400 series
Stainless steel-backed full glass door
Width 60 cm
Left-hinged
Controls at the top

BM454110
Combi-microwave oven 400 series
Stainless steel-backed full glass door
Width 60 cm
Right-hinged
Controls at the bottom

BM455110
Combi-microwave oven 400 series
Stainless steel-backed full glass door
Width 60 cm
Left-hinged
Controls at the bottom

BM450110
Combi-microwave oven 400 series
Stainless steel-backed full glass door
Width 60 cm
Right-hinged
Controls at the top

Handleless door / automatic door opening
Single operation and combination of microwave, grill and oven
Sequential operation of up to 5 modes incl. programming of combined operation and rest time
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control
Interior volume 36 litres

Programmes
Microwave operation with 5 output levels: 1000, 600, 360, 180, 90 W.
Oven operation with 4 heating methods: Hot air 40 °C and from 100 °C to 250 °C,
Full surface grill + hot air from 100 °C to 250 °C,
Full surface grill + circulated air from 100 °C to 250 °C
Full surface grill with 3 levels of intensity, maximum output 2000 W.
Heating methods with microwave output levels 600, 360, 180 and 90 W freely combinable.
15 automatic programmes with weight indication, customisable:
4 defrosting programmes
4 cooking programmes
7 combination programmes
Option to save individual recipes.

Handling
Automatic door opening.
Rotary knob and TFT touch display operation.
Clear text display in 25 languages.
Information key with use indications.
Side-opening door opens up to 180° angle.

Features
Innowave.
Rapid heating.
4 rack levels.
Actual temperature display.
60 W halogen light on the side.

Safety
Thermally insulated door with triple glazing.
Triple door lock.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning
Hygienic stainless steel interior with glass ceramic base.
Interior back wall with catalytic coating.

Planning notes
Door hinge not reversible.
Plan the niche without back wall.
The door panel surface of the appliance extends 47 mm from the furniture cavity.
If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 94 mm from the furniture cavity.
Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.

Characteristics
Type of micro-wave oven
MW-Combi
Type of control
Electronic
Color / Material Front
Stainless steel
Dimensions of the product (mm)
455 x 590 x 582
Cavity dimensions (mm)
236.0 x 445.0 x 348.0
Length of electrical supply cord (cm)
150
Net weight (kg)
39.0
Gross weight (kg)
44.0

Consumption and connection features
Maximum micro-wave power (W)
1000
Power of the booster function (W)
Connection rating (W)
3100
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
60; 50
Plug type
fixed connection, no plug

created on 2015-04-13
Page 1

The mains socket needs to be planned outside of the built-in niche.

Connection
Total connected load 3.1 kW.
Connection cable 1.5 m without plug.

Side view of BS 454/455, BM 454/455 above BO

