



Color Variants

BOP220101
Full glass door in Gaggenau Anthracite
Width 60 cm
BOP220111
Full glass door in Gaggenau Metallic
Width 60 cm
BOP220131
Full glass door in Gaggenau Silver
Width 60 cm

Included accessories

1 x enamel baking tray.
suit. pyrol. clean..
1 x glass pan.
1 x grill shelf.

Optional accessories

BA056133
Baking stone
BS020002
Pizza paddle, set of 2
GN340230
Gastronorm roaster in cast aluminium

Product Variants

BOP221101
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Left-hinged

BOP220101
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Right-hinged

Flush installation
Pyrolytic system
9 heating methods, with baking stone function
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 50 °C to 300 °C

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top heat.
Bottom heat.
Hot air+ bottom heat.
Full surface grill + circulated air.
Full surface grill.
Baking stone function.

Handling

Rotary knob and TFT touch display operation.
Clear text display in 25 languages.
Option to save individual recipes.
Information key with use indications.
Side-opening door opens up to 110° angle.

Features

Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated air cleaning catalyser.

Planning notes

Door hinge not reversible.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.
For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
The mains socket needs to be planned outside of the built-in niche.

Connection

Characteristics
Color / Material Front
Anthracite
Construction type
Built-in
Integrated Cleaning system
Pyrolytic
Required niche size for installation (HxWxD)
590 x 560 x 550
Dimensions of the product (mm)
595 x 590 x 547
Control Panel Material
without panel
Door Material
Glass
Net weight (kg)
55.0
Usable volume of cavity (l)
76
Cooking method first cavity
First cavity material
Temperature control
electronic
Number of interior lights
1
Approval certificates
CE, VDE
Length of electrical supply cord (cm)

Consumption and connection features
Number of cavities (2010/30/EC)
1
Energy efficiency class (2010/30/EC)
A
Energy consumption per cycle conventional (2010/30/EC)
1.25
Energy consumption gas oven per cycle conventional (2010/30/EC)
Energy consumption per cycle forced air convection (2010/30/EC)
0.92
Energy consumption gas oven per cycle forced air convection (2010/30/EC)
Energy efficiency index (2010/30/EC)
105.7
Electrical connection rating (W)
3700
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
fixed connection, no plug
created on 2015-04-09
Page 1

Total connected load 3.7 kW.
Plan a connection cable.

GAGGENAU

