

Color Variants BOP250101 Full glass door in Gaggenau Anthracite Width 60 cm BOP250111 Full glass door in Gaggenau Metallic Width 60 cm BOP250131 Full glass door in Gaggenau Silver Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrol. clean.. 1 x glass pan. 1 x grill shelf. 1 x pluggable meat probe.

Optional accessories BA056133 Baking stone BS020002 Pizza paddle, set of 2 GN340230 Gastronorm roaster in cast aluminium

Product Variants BOP251101 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm Left-hinged BOP250101 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm Right-hinged

Flush installation Pyrolytic system 13 heating methods, with core temperature probe and baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 300 °C

Heating methods

Hot air. Eco hot air. Top heat. Top heat. Bottom heat. Hot air+ bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting.

Handling

Rotary knob and TFT touch display operation. Clear text display in 25 languages. Option to save individual recipes (incl. core temperature probe). Information key with use indications. Side-opening door opens up to 110° angle.

Features

Core temperature probe with automatic shut-off. Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. 60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Pyrolytic system. Gaggenau enamel. Heated air cleaning catalyser.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture cavity. Necessary lateral gap between appliance door and furniture panel of min. 5 mm. Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance. When planning a corner solution, pay attention to the 110° door opening angle.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account. Characteristics Color / Material Front Anthracite Construction type Built-in Integrated Cleaning system Pyrolytic Required niche size for installation (HxWxD) 590 x 560 x 550 Dimensions of the product (mm) 595 x 590 x 547 Control Panel Material without panel Door Material Glass Net weight (kg) 55.0 Usable volume of cavity (I) 76 Cooking method first cavity First cavity material Temperature control electronic Number of interior lights

Approval certificates CE, VDE Length of electrical supply cord (cm)

Consumption and connection features Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC) 1.25

Energy consumption gas oven per cycle conventional (2010/30/EC) Energy consumption per cycle forced

air convection (2010/30/EC) 0.92

Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC) 105.7

Electrical connection rating (W) 3700

Current (A)

Voltage (V) 220-240

Frequency (Hz)

Plug type

fixed connection, no plug created on 2015-04-09

Page 1

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Connection

Total connected load 3.7 kW. Plan a connection cable.



BOP250101 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm Right-hinged created on 2015-04-09 Page 2



